



# 35C 15/17/21 V (/P)





## **DIMENSIONS (mm)**

WHEELBASE (A)	30	000	300	00L	33	00	39	50
ROOF	H1	H2	H1	H2	H2	H3	H2	H3
Volume (m <sup>3</sup> )	7.3	9	8.3	10.2	12	13.2	15.6	17.2
B Overall length	50	)77	54	77	59	97	70	12
K Overall height (unladen)	2335	2705	2335	2705	2705	2910	2705	2910
M Front track				17	'40			
N Rear track				15	640			
P Ground clearance min. Front (laden)				1	15			
P Ground clearance min. Front (unladen)				1	54			
C Front overhang				99	98			
D Rear overhang	10	)79	14	79	16	99	20	)64
Turning Circle (K to K):	10	380	103	380	11:	240	13	160
Turning Circle (Wall to wall):	11	500	11	500	124	400	14:	300
CARGO AREA								
Interior length	26	600	30	00	35	20	45	60
Interior width				18	800			
Interior Height	1545	1900	1545	1900	1900	2100	1900	2100
Dist. Between wheel arches (inter.)	1030							
Height of wheel arches	280							
S Height of loading area (/ P)				735 (700	+70/-50)			
REAR DOOR								
Opening width				15	540			
Opening height	1430	1780	1430	1780	1780	1990	1780	1990
SIDE LOAD DOOR								
Opening width	1100		1250					
Opening height	1415	1780	1415	1780		17	'80	
WEIGHTS (kg)								
GVW				35	600			
GTW	7000							
Front Axle plated wieght	1800							
Rear Axle plated weight	2600							
Unbraked Trailer towing capacity	750							
Braked Trailer towing capacity				35	600			
Kerb Weight	2165	2189	2206	2230	2305	2340	2430	2470
Kerb weight front axle	1324	1324	1291	1291	1310	1310	1350	1350
Kerb weight rear axle	841	864	916	939	995	1030	1080	1120
Load capacity max. (97/27)	1335	1311	1294	1270	1195	1160	1070	1030

FUEL CONSUMPTION & CO2		Combine	d I/100Km
	Engine	Max	Min
Manual	0.15		
Automated	0.15		
Manual	0.17		
Automated	0.17		
Manual	0.21		
Automated	0.21		

Combined MPG			
Max	Min		

Max	Min

Combined CO2

Weights are in working order EC 97/27 (tolerance + / - 5%) for the performance standard with full tank of fuel, spare wheel, tools and with the driver. Fuel consumption and CO2 in accordance with EEC/ECE NEDC cycle, actual figures may vary accoring to body type, axle ratio and tyres fitted.





## 35C 15/17/21 V (/P)

ENGINE	3.0 litre	EURO 5 (LD)		
	4-stroke, direct injection with turbo			
	intercooler and Waste Gate (.15 WG)			
	turbine variable (.17 VGT).			
	Twin Stage Turbo (.21 TST)			
	Exhaust gas treatment EGR.			
	16 valves, timing chain.			
Number of cylinders:	4 inline			
Bore x stroke:	95,8 x 104 mm			
Total displacement:	3000 cc			
Compliant Standards	s EEC 97/21			
Particulate Filter:	Standard			
Torque:	kW/Hp R/min	Nm R/min		
.15	107/146 (3000-3500)	350 (1500-2600)		
.17	125/170 (3000-3500)	400 (1250-2600)		
.21	150/205 (3000-3500)	470 (1400-2600)		
CLUTCH				
Single dry plate hydr	aulically operated.			
Diameter: 11" (279	,5 mm).17 & 12" (305	mm).21		
GEARBOX				
6 speed sychromesh 2840.6 OD				
1 st speed:	5 373 1			

1.st speed:	4,655:1
6 speed sychromes	sh 2850.6 OD (standard .21 engine)
Reverse:	4,838:1
6.th speed:	0,791:1
r.st speed.	5,373.1

	.,
6.th speed:	0,685:1
Reverse:	4,189:1

## 6 speed sychromesh 6AS400 OD

5,373:1 0,791:1

4,838:1

1.st speed: 6.th speed: Reverse:

## **CONSTRUCTION & FINISH**

C - section steel longitudinal side members and tubular cross members (Fe420, dimensions 180x69x3), with pressed steel unitary body mounted on rubber bushes. Anti corrosion process includes full cataphoretic dipping & galvanised box sections along with zinc plated panels in all vulnerable areas. Full undersealing. CAB INTERIOR

The fully trimmed comfort cab is quiet, spacious and fully equipped and includes:

-Driver's airbag with seatbelt pretensioners -Dual passenger bench seat with 3 points seatbelts on

all seats.

-Driver's seat adjustable for height, reach & rake -Headrests on all seats, electric windows

-Tinted glass, cupholders both sides, Bottle holders in doors -A4 size storage compatment, Glove box -Adjustable steering column

## VENTILATION SYSTEM

-Four speed fan air blending system + recirculation -Four facial air outlet nozzles, windscreen & side demist DASHBOARD INCLUDES

-Dash mounted gear lever, RDS stereo radio CD -Speedometer and tachometer -Provision for tachograph and additional radio slot

-Water temperature gauge & LCD display includes: Journey trip computer for distance, journey time,

fuel consumption & clock

-Warning lights & headlamp orientation

## CAB EXTERIOR

Sturdy chassis mounted front bumper and sacraficial plastic lower side panels - full length Left hand side sliding door & 180 degree rear doors Large exterior rear view mirrors with double size wide angle mirror, Full width rear step

## BRAKES

DITAKES		
Front and rear disc		der, ESP9, EBD and ASR.
	Front	Rear
Ø disc (mm):	290	290
Service brake:		
	ium assistance, dia	gonal circuit.
Wear indicator on t	he front and rear.	
Hand brake:		
Handbrake on the	ear discs.	
STEERING		
Rack and pinion wi	th hydraulic assista	nce,
Steering wheel Ø 4	20mm, steering loc	k
ELECTRICAL INS	<b>FALLATION</b>	
Alternator:	14V - 120 A	
Battery:	12V - 110 Ah	
SUSPENSION		
Front:	Parabolic transve	erse leaf.
Rear:	2 Leaf parab. + a	intiroll bar.
Rear air:	2 bag auto self le	eveling with antiroll bar &
	stationary raise /	lower facility
Shock	Hydraulic telesco	pic reinforced
absorbers:	front and rear	
WHEELS AND TIR	ES	
195/65 R 16 Loadi	ndex 104/102	
FUEL TANK		
70L plastic left side		
SECURITY		
-Desmodromic key	s & locks, steering l	ock,immobiliser
-Unglazed full stee	bulkhead to Din 75	410, unglazed rear doors
LOAD AREA		
Floor-steel ribbed w	vith DIN load lashing	g rings
Sides internally reinforced with DIN lower load lahing rings		
Side sliding door & 180 degree rear doors.		
MODEL VADIANT	•	

## MODEL VARIANTS

**DAILY PLUS specification additionally includes:** Central locking, Cruise control, TOMTOM provision Heated and electrically adjustable rear view mirrors. Overwindscreen storage + din slot.

## DAILY TOP specification further adds:

Full cab climate control (aircon), Suspended driver's seat, Storage box under dual passenger bench, Fog lights

## **OPTION PACKS Van**

#### Special van pack:

270degree rear doors, Bulkhead with fixed window, Reverse sensors in rear step & 3rd stop light with rear spot light.

## - Super van pack:

Third stop light, rear spot light and rear camera, wooden floor.

## - Towing pack:

13 pin elctrical towing socket, 140amp alternator 50mm ball tow bar and Tachograph. 140 Ampere alternator Digital tachograph (std above 3.5t)

## - Winter pack

Heated windscreen Heated and elctric mirrors Webasto cab and engine heater 110 AH battery Heated induction system,