


DAILY

35S 17/21 V (/P)



DIMENSIONS (mm)

WHEELBASE (A)		3000		3000L		3300		3950	
ROOF		H1	H2	H1	H2	H2	H3	H2	H3
Volume (m³)		7.3	9	8.3	10.2	12	13.2	15.6	17.2
B Overall length		5077		5477		5997		7012	
K Overall height (unladen)		2270	2645	2270	2645	2640	2825	2670	2860
M Front track		1740							
N Rear track		1690							
P Ground clearance min. Front (laden)		143							
P Ground clearance min. Front (unladen)		180							
C Front overhang		998							
D Rear overhang		1079		1479		1699		2064	
Turning Circle (K to K) :		10380				11240		13160	
Turning Circle (Wall to wall) :		11500				12400		14300	
CARGO AREA									
Interior length		2600		3000		3520		4560	
Interior width		1800/1750							
Interior Height		1545	1900	1545	1900	1900	2100	1900	2100
Dist. Between wheel arches (inter.)		1320							
Height of wheel arches		280							
S Height of loading area (/ P)		695 (620)							
REAR DOOR									
Opening width		1540							
Opening height		1430	1780	1430	1780	1780	1990	1780	1990
SIDE LOAD DOOR									
Opening width		1100				1250			
Opening height		1415	1780	1415	1780	1780			
WEIGHTS (kg)									
GVW		3500							
GTW		6300							
Front Axle plated weight		1800							
Rear Axle plated weight		2240							
Unbraked Trailer towing capacity		750							
Braked Trailer towing capacity		2800							
Kerb Weight		2060	2075	2080	2115	2190	2220	2315	2355
Kerb weight front axle		1285	1285	1255	1250	1270	1270	1315	1315
Kerb weight rear axle		775	790	825	865	920	950	1000	1040
Load capacity max. (97/27)		1440	1425	1420	1385	1310	1280	1185	1145

FUEL CONSUMPTION & CO2		Combined l/100Km	
	Engine	Max	Min

Manual	0.17		
Automated	0.17		
Manual	0.21		

Combined MPG	
Max	Min

Combined CO2	
Max	Min

Weights are in working order EC 97/27 (tolerance + / - 5%) for the performance standard with full tank of fuel, spare wheel, tools and with the driver.
Fuel consumption and CO2 in accordance with EEC/ECE NEDC cycle, actual figures may vary according to body type, axle ratio and tyres fitted.

IVECO
TRANSPORT IS ENERGY

ENGINE	3.0 litre	EURO 5 (LD)
	4-stroke, direct injection with turbo intercooler and variable turbine (.17 VGT) Twin Stage Turbo (.21 TST) Exhaust gas treatment EGR. 16 valves, timing chain.	
Number of cylinders:	4 inline	
Bore x stroke:	95,8 x 104 mm	
Total displacement:	3000 cc	
Compliant Standards:	EEC 97/21	
Particulate Filter:	Standard	
Torque:	kW/Hp	R/min Nm R/min
.17	125/170 (3000-3500)	400 (1250-2600)
.21	150/205 (3000-3500)	470 (1400-2600)

CLUTCH

Single dry plate hydraulically operated.

Diameter: 11" (279,5 mm).17 & 12" (305 mm).21

GEARBOX**6 speed sychromesh 2840.6 OD**

Standard .17 engine

1.st speed: 5,373:1

6.th speed: 0,791:1

Reverse: 4,838:1

6 speed sychromesh 2850.6 OD (standard .21 engine)

1.st speed: 4,655:1

6.th speed: 0,685:1

Reverse: 4,189:1

6 speed sychromesh 6AS400 OD

Optional automated - all engines (ex .21).

1.st speed: 5,373:1

6.th speed: 0,791:1

Reverse: 4,838:1

CONSTRUCTION & FINISH

C - section steel longitudinal side members and tubular cross members, with pressed steel unitary body mounted on rubber bushes. Anti corrosion process includes full cataphoretic dipping & galvanised box sections along with zinc plated panels in all vulnerable areas.

Full undersealing.

CAB INTERIOR

The fully trimmed comfort cab is quiet, spacious and fully equipped and includes:

- Driver's airbag with seatbelt pretensioners
- Dual passenger bench seat with 3 points seatbelts on all seats.
- Driver's seat adjustable for height, reach & rake
- Headrests on all seats, electric windows
- Tinted glass, cupholders both sides, Bottle holders in doors
- A4 size storage compartment, Glove box
- Adjustable steering column

VENTILATION SYSTEM

- Four speed fan air blending system + recirculation
- Four facial air outlet nozzles, windscreen & side demist

DASHBOARD INCLUDES

- Dash mounted gear lever, RDS stereo radio CD
- Speedometer and tachometer
- Provision for tachograph and additional radio slot
- Water temperature gauge & LCD display includes: Journey trip computer for distance, journey time, fuel consumption & clock
- Warning lights & headlamp orientation

CAB EXTERIOR

Sturdy chassis mounted front bumper and sacrificial plastic lower side panels - full length
Left hand side sliding door & 180 degree rear doors
Large exterior rear view mirrors with double size wide angle mirror, Full width rear step

BRAKES

Front and rear discs with ABS, Hill Holder, ESP9, EBD and ASR.

	Front	Rear
Ø disc (mm):	300	296

Service brake:

Hydraulic with vacuum assistance, diagonal circuit.

Wear indicator on the front and rear.

Hand brake:

Handbrake on the rear discs.

STEERING

Rack and pinion with hydraulic assistance,

Steering wheel Ø 420mm, steering lock

ELECTRICAL INSTALLATION

Alternator: 14V - 120 A

Battery: 12V - 110 Ah

SUSPENSION

Front: Parabolic transverse leaf.

Rear: A single parabolic with antiroll bar

Rear air: 2 bag auto self leveling with antiroll bar & stationary raise / lower facility

Shock absorbers: Hydraulic telescopic reinforced front and rear

WHEELS AND TIRES

225/65 R 16 Loadindex 112/110

FUEL TANK

70L plastic left side.

SECURITY

-Desmodromic keys & locks, steering lock, immobiliser

-Unglazed full steel bulkhead to Din 75410, unglazed rear doors

LOAD AREA

Floor-steel ribbed with DIN load lashing rings

Sides internally reinforced with DIN lower load lashing rings

Side sliding door & 180 degree rear doors.

MODEL VARIANTS**DAILY PLUS specification additionally includes:**

Central locking, Cruise control, TOMTOM provision
Heated and electrically adjustable rear view mirrors.
Overwindscreen storage + din slot.

DAILY TOP specification further adds:

Full cab climate control (aircon), Suspended driver's seat, Storage box under dual passenger bench, Fog lights

OPTION PACKS Van**- Special van pack:**

270degree rear doors , Bulkhead with fixed window, Reverse sensors in rear step & 3rd stop light with rear spot light.

- Super van pack:

Third stop light, rear spot light and rear camera, wooden floor.

- Towing pack:

13 pin electrical towing socket, 140amp alternator
50mm ball tow bar and Tachograph.
140 Ampere alternator
Digital tachograph

- Winter pack

Heated windscreen
Heated and electric mirrors
Webasto cab and engine heater
110 AH battery
Heated induction system,